



CONCRETE MOISTURE SOLUTIONS, INC.
"An Affiliate of Barrier One, Inc."

Phone: 877.224.5850
Fax: 866.594.3490
640 Garden Commerce Parkway
Winter Garden, Florida 34787



BARRIER ONE INTERNATIONAL
MOISTURE VAPOR REDUCTION ADMIXTURE

Email: info@cmsadmix.com
info@barrierone.com
Website: www.cmsadmix.com

Benefits

- The industries only available “life of the concrete” warranty
- Unmatched project specific quality control process
- Unmatched adhesion guarantee
- Most cost effective approach of mitigating liability due to concrete moisture
- **COMPLETELY** compatible with both normal and lightweight mix designs
- Requires no further field moisture testing but if conducted, warranted up to 100% RH per ASTM F2170 and/or 25 lbs per ASTM F1869
- Compatible with all floor coverings, adhesives for non-porous substrates, coatings and roofing membranes
- Certified shrink reduction admixture (SRA) per ASTM C-157
- Certified alkali silica reaction (ASR) inhibitor per ASTM C-1260
- Requires only 1 to 3 days curing with plastic sheet or waterproof paper
- Install slab coverings (flooring or roofing material) in as little as 9 DAYS after slab placement, assuming all other conditions for installation are met.
- ZERO moisture vapor emission flooring failures
- No project delays due to moisture vapor emission
- No financial catastrophe due to forced remediation and lost opportunity cost
- Contributes several points toward LEED Certification when used in a system